

# Kanlux

EAN: 5905339392312

## Surface-mounted LED panel Kanlux 39231 BLINGO UAIO SRM40W 60



Date of issue: 17.02.2026, 12:16

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland [kanlux@kanlux.com](mailto:kanlux@kanlux.com)

EN

## PRODUCT PARAMETERS

Rated voltage [V]	220-240 AC
Rated frequency [Hz]	50
Maximum power [W]	max 40
Power factor	0.98
Luminous flux of the light fitting [lm]	3990/4370/4210
Correlated colour temperature [K]	3000/4000/6500
Power setting range [W]	31-40
Luminous flux setting range [lm]	3300-4370
Lighting angle [°]	90
Diode type	LED SMD
Integrated LED light source	yes
Colour consistency in McAdam ellipses	6
Colour temperature	warm white, white, cold white
Colour rendering index	90
Service life [h]	50000
Luminous-flux-retention factor at the end of rated service life	L70B50
Number of on/off cycles	≥50000
Place of application	Indoors
IP class	20
Compatible with a dimmer	no
Feeder included	yes
Supply-cord type	direct current
UGR	<19
LED light source replaceability	Possibility of replacing the LED light source only by qualified personnel (only by the manufacturer service)
Control gear replaceability	Possibility of replacing the control equipment only by qualified personnel (only by the manufacturer service)
Product category according to 2019/2020/EU	Containing product (CP)
Mercury content in the lamp [mg]	0

## DIMENSIONS AND MOUNTING

Height [mm]	40
Width [mm]	595
Length [mm]	595
Place of assembly	ceiling mounted
Range of sections of wires used [mm <sup>2</sup> ]	0,75-2,5

## MATERIAL AND CONSTRUCTION

Colour	white
Enclosure material	steel
Lampshade material	plastic
Panel/frame material	steel
Class of protection against electric shock	I
Kształt	square
Minimum distance from the illuminated object	0,5m
Ambient temperature range to which the product can be exposed	5÷25

## LIGHT SOURCE PARAMETERS

On-mode power of the light source Pon [W]	6
Energy consumption in on-mode of the light source (kWh/1000h)	6
Energy efficiency class of the light source in the contains product (CP)	D
Number of modules (LED light source)	6

## LOGISTICS

Unit of measurement	unit
Packaging method	5
Number of units in the secondary packaging	1
Number of units in the packaging	5
Net unit weight [g]	1602

Date of issue: 17.02.2026, 12:16

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

